



aerospace
climate control
electromechanical
filtration
fluid & gas handling
hydraulics
pneumatics
process control
sealing & shielding



1-1/2" I.D. hose!

Parker Industrial Hose

E-Z Form™ Series 7395, 7219



ENGINEERING YOUR SUCCESS.

Parker E-Z Form™ Hose



Series 7395, 7219

Extreme Flexibility

Specify Parker E-Z Form hose for installations where tight bends exceed the bend radius of other hoses; where the application might otherwise indicate specifying a formed hose. In fact, E-Z Form hose is an economical alternative to formed hose—with a lower product cost, reduced inventory required for multiple applications and for immediate installation because there is no design, fabrication time or tooling required.

- **Extremely flexible—replace formed hoses**
- **Full-flow performance without kinks**
- **No tooling or production minimum quantities**
- **Multi-purpose (MP) products feature an oil-resistant nitrile inner tube, reinforcing plies with a helical wire, and a neoprene cover**
- **General Service (GS) products feature an EPDM inner tube and cover with reinforcing plies with a helical wire**
- **Full vacuum or suction use**

Packaging

Standard packaging is 25-foot coils. Coil lengths available up to 130 ft.

Couplings

Refer to CrimpSource at www.safehose.com for crimp specifications and coupling recommendations.

E-Z Form™ GS Hose • Series 7395

Tube:	EPDM
Reinforcement:	Textile Plies and Helical Wire
Cover:	Greek Corrugated EPDM
Temp Range:	-40°F to +257°F (-40°C to +125°C)
Branding:	PARKER SERIES 7395 E-Z FORM GS HOSE 75 PSI MAX WP
Brand Type:	Blue Mylar Tape with Black Letters
Vacuum Rating:	Full
Specifications:	SAE J20R1 D-1



E-Z Form™ MP Hose • Series 7219

Tube:	Nitrile
Reinforcement:	Textile Plies and Helical Wire
Cover:	Greek Corrugated Neoprene
Temp Range:	-20°F to +180°F (-29°C to +82°C)
Branding:	PARKER SERIES 7219 E-Z FORM MP HOSE 75 PSI MAX WP
Brand Type:	Red Mylar Tape with Black Letters
Vacuum Rating:	Full



Series 7395 E-Z Form GS

Part Number	Size (in.)	Inside Diameter (in.)	Inside Diameter (mm)	Outside Diameter (in.)	Outside Diameter (mm)	Max Rec WP (psi)	Length [†] (ft.)	Weight (lbs./ft.)	Min. Bend Radius (in.)
7395-0500025	1/2	0.512	13	0.906	23	75	25	0.23	1.4
7395-0594025	19/32	0.591	15	0.984	25	75	25	0.25	1.8
7395-0625025	5/8	0.630	16	1.024	26	75	25	0.27	1.8
7395-0688025	11/16	0.709	18	1.102	28	75	25	0.29	1.8
7395-0750025	3/4	0.748	19	1.142	29	75	25	0.31	2.0
7395-0813025	13/16	0.787	20	1.181	30	75	25	0.32	2.0
7395-1000025	1	0.984	25	1.378	35	75	25	0.38	2.0
7395-1125025	1-1/8	1.102	28	1.496	38	75	25	0.42	2.6
7395-1188025	1-3/16	1.181	30	1.575	40	75	25	0.45	3.0
7395-1250025	1-1/4	1.260	32	1.693	43	75	25	0.50	3.1
7395-1375025	1-3/8	1.378	35	1.811	46	75	25	0.54	3.7
7395-1500025	1-1/2	1.496	38	1.929	49	75	25	0.58	3.9
7395-1563025	1-9/16	1.575	40	2.008	51	75	25	0.61	4.3
7395-1625025	1-5/8	1.654	42	2.087	53	75	25	0.64	4.7
7395-1750025	1-3/4	1.772	45	2.205	56	75	25	0.68	5.1
7395-2000025	2	2.008	51	2.480	63	75	25	0.96	5.9
7395-2188025	2-3/16	2.165	55	2.638	67	75	25	1.03	7.1
7395-2250025	2-1/4	2.283	58	2.756	70	75	25	1.08	7.9
7395-2375025	2-3/8	2.362	60	2.874	73	75	25	1.11	8.3
7395-2500025	2-1/2	2.500	64	3.012	77	75	25	1.17	8.7
7395-2563025	2-9/16	2.559	65	3.071	78	75	25	1.19	9.0
7395-2750025	2-3/4	2.756	70	3.307	84	75	25	1.40	9.8
7395-3000025	3	2.992	76	3.543	90	75	25	1.51	10.6
7395-3125025	3-1/8	3.150	80	3.701	94	75	25	1.57	11.8
7395-3375025	3-3/8	3.346	85	3.937	100	75	25	1.74	12.9
7395-3500025	3-1/2	3.504	89	4.094	104	75	25	1.92	13.6
7395-3563025	3-9/16	3.543	90	4.134	105	75	25	1.96	13.8
7395-4000025	4	4.016	102	4.567	116	75	25	2.20	15.7

Series 7219 E-Z Form MP

Part Number	Size (in.)	Inside Diameter (in.)	Inside Diameter (mm)	Outside Diameter (in.)	Outside Diameter (mm)	Max Rec WP (psi)	Length [†] (ft.)	Weight (lbs./ft.)	Min. Bend Radius (in.)
7219-0500025	1/2	0.512	13	0.906	23	75	25	0.23	1.4
7219-0594025	19/32	0.591	15	0.984	25	75	25	0.25	1.8
7219-0625025	1/2	0.630	16	1.024	26	75	25	0.27	1.8
7219-0688025	11/16	0.709	18	1.102	28	75	25	0.29	1.8
7219-0750025	3/4	0.748	19	1.142	29	75	25	0.31	2.0
7219-0813025	13/16	0.787	20	1.181	30	75	25	0.32	2.0
7219-1000025	1	0.984	25	1.378	35	75	25	0.38	2.0
7219-1125025	1-1/8	1.102	28	1.496	38	75	25	0.42	2.6
7219-1188025	1-3/16	1.181	30	1.575	40	75	25	0.45	3.0
7219-1250025	1-1/4	1.260	32	1.693	43	75	25	0.50	3.1
7219-1375025	1-3/8	1.378	35	1.811	46	75	25	0.54	3.7
7219-1500025	1-1/2	1.496	38	1.929	49	75	25	0.58	3.9
7219-1563025	1-9/16	1.575	40	2.008	51	75	25	0.61	4.3
7219-1625025	1-5/8	1.654	42	2.087	53	75	25	0.64	4.7
7219-1750025	1-3/4	1.772	45	2.205	56	75	25	0.68	5.1
7219-2000025	2	2.008	51	2.480	63	75	25	0.96	5.9
7219-2188025	2-3/16	2.165	55	2.638	67	75	25	1.03	7.1
7219-2250025	2-1/4	2.283	58	2.756	70	75	25	1.08	7.9
7219-2375025	2-3/8	2.362	60	2.874	73	75	25	1.11	8.3
7219-2500025	2-1/2	2.500	64	3.012	77	75	25	1.17	8.7
7219-2563025	2-9/16	2.559	65	3.071	78	75	25	1.19	9.0
7219-2750025	2-3/4	2.756	70	3.307	84	75	25	1.40	9.8
7219-3000025	3	2.992	76	3.543	90	75	25	1.51	10.6
7219-3125025	3-1/8	3.150	80	3.701	94	75	25	1.57	11.8
7219-3375025	3-3/8	3.346	85	3.937	100	75	25	1.74	12.9
7219-3500025	3-1/2	3.504	89	4.094	104	75	25	1.92	13.6
7219-3563025	3-9/16	3.543	90	4.134	105	75	25	1.96	13.8
7219-4000025	4	4.016	102	4.567	116	75	25	2.20	15.7

† Chart shows stocked 25-ft lengths. Both Series 7219 and 7395 can be ordered in up to 130-ft lengths. Contact Parker for details and part numbers.

